



4700

IN-LINE SLIDER / LIFT & SLIDE TBB

ENERGY EFFICIENCY

Thermal Transmission Coefficient

$U_w \geq 1.0$ (W/m²K)

Please consult typology, dimensions and glazing.

ACCOUSTIC INSULATION

Maximum glazing: **36 mm**

Maximum acoustic insulation: **R_w = 40 dB**

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (EN 12207):

Class 3* / 4**

Water tightness (EN 12208):

Class 7A

Wind resistance (EN 12210):

Class C5* / C2**

* Reference in-line slider test 1,8 x 2,2 m / 2 sashes

** Reference lift & slide test 4,0 x 2,50 m / 2 sashes

Security Test: **PAS24** ☒

Passed

Reference test 2,40 x 2,40 m / 2 sashes

SECTIONS	Frame 120 mm and 115 mm Three-rail 185 mm Sash 50 mm
PROFILE THICKNESS	Balcony 1.5 mm
MAXIMUM DIMENSIONS	Width (L) = 2.500 mm Height (H) = 3.000 mm
MAXIMUM WEIGHT/SASH	Slide 280 Kg Lift & Slide 300 Kg

Please consult maximum dimensions according to types.

EXTRUSION ALLOY
6063 T-5
POLYAMIDE STRIP LENGTH
Polyamide 6.6 reinforced with 25% fiberglass : 20 y 25 mm
OPENING POSSIBILITIES
Sliding of 2, 3, 4, 6 & 8 sashes 1 rail (1 sash + 1 fixed light) 2, 3 & 4 rails Galandage 1, 2, 3 & 4 sashes

FINISHES

Colour powder coating
(RAL, mottled, rough...)

According to Qualicoat > 60 microns

Wood effect powder coating

According to Qualideco standard

Anodized

According to Ewwa Euras

Standard Class 15

Optionally Class 20 and 25

Optionally bicoloured

